

Version	2.0	Date	9/22/20
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Commercial Recessed Light
Item Number	9468
Stock Code	LED10CRL30SW-270L9CCT3/MV
Mounting	10" Recessed
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	18 / 23 /30	Replacement Wattage (W)	150-250
Tested Wattage (W)	30		
Input Voltage (V)	120-277	Surge Protect Level	2KV
Voltage Frequency (Hz)	60	Dimmable	0-10V
Input Current (A)	0.25 (@120V)	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	1,620 2,070 2,700	CCT (K)	3CCT (30/40/50K)
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	>90		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	5°F ~ 113°
Storage Temperature (°F)	5°F ~ 113°
IP Rating	Wet Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7337	BAEM25-170BC/347-C	25W Micro Inverter 120-347V with 12" Conduit
P10426	MT-TBAR-EM-2ft	T-Grid Hanger for Emergency Driver
P10309	PLT-NC/6DL	6" Round Mounting Plate
P10318	PLT-NC/8DL-LONG	8" Round Mounting Plate
P10375	PLT-NC-DL/3-4-6-8	Universal Plate 3/4/6/8"

PRODUCT DIMENSIONS		
Width- in / (mm)	11.22"	285
Height- in / (mm)	5.05"	128.3
Depth- in / (mm)	-	-
EPA (ft²)	-	-
Weight (lbs)	1.98	
Mounting Height (ft)	-	
Cable Length (ft)	-	



CERTIFICATIONS			
UL/ETL	UL/cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star	✓	FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS