

Version	2.0	Date	10/23/20
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Downlight
Item Number	9524
Stock Code	LED4RL9-55L930
Mounting	4" Recessed
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	9	Replacement Wattage (W)	60
Tested Wattage (W)	9		
Input Voltage (V)	120V	Surge Protect Level	2.5KV
Voltage Frequency (Hz)	60	Dimmable	Yes
Input Current (A)	0.1	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	550	CCT (K)	3000K
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	>90		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	14°F ~ 104°
Storage Temperature (°F)	14°F ~ 104°
IP Rating	Wet Location
IK Rating	-
Rated Life (Hrs)	35,000
Warranty (Yrs)	3

ACCESSORIES		
Item #	Stock Code	Description
7337	BAEM25-170BC/347-C	25W Micro Inverter 120-347V with 12" Conduit

PRODUCT DIMENSIONS		
Width- in / (mm)	5.04" 128	
Height- in / (mm)	1.85" 47.2	
Depth- in / (mm)	5.04" 128	
EPA (ft²)	-	
Weight (lbs)	0.31	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	✓
NSF/ETL Sanitation		JA8	✓
Energy Star	✓	FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS