


natural^{led}®

Product Engineering Spec

Product Spec			
Category	LED Wall Pack	PICTURE	
Item Code	9533		
Stock Code	FXTWP100SW/CCT3/BZ/347-PHO		
Mounting	Wall Mount		
Housing Color	Bronze		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	100 / 80 / 60	Lumen (lm)	14500 / 11600 / 8700
Tested Wattage (W)	100 / 80 / 60	Efficacy (lm/w)	145 / 140 / 135
Input Voltage (V)	120~347	CRI	80
Voltage Frequency (Hz)	50/60	CCT (K)	5000 / 4000 / 3000
Input Current (A)	0.84 / 0.67 / 0.5 (@120V)	Beam Angle (°)	Forward Throw
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	400~750	Operating Temperature	-40°F~122°F
Surge protect level	4KV	Storage Temperature	-40°F~140°F
Dimmable	0-10V	IP rating	IP65
THD	≤20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)	9.26	120~277V AC Microwave Sensor - Item# P10234	
Height (in)	9.16		
Depth	7.69		
Width (in)	14.29		
Mounting Height (ft)			
Cable Length (ft)			

Qualifications			
UL/ETL	ETL/cETL	LM79	√
Energy Star		LM80	√
DLC	V5.1 Premium	IES File	√
CEC		FDA	
JA8		NEMA	
FCC	√	Dimmer List	
RoHS	√		

Comments:

Photocell Included with Fixture