

Version	2.0	Date	3/26/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Utility Wrap
Item Number	9538
Stock Code	FXUWS27/48CL/840
Mounting	Ceiling Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	27	Replacement Wattage (W)	4 x 32W T8
Tested Wattage (W)	27		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	0.25	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	3,510	CCT (K)	4000K
Efficacy (lm/w)	130	Beam Angle (°)	110°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 122°
Storage Temperature (°F)	-22°F ~ 122°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
K7336197	FXUWS-BAEM-MT	Emergency Driver Kit
P10234	SEN-MC605V-D	Motion/Photocell Sensor 120-277V
P10249	WG-UWS/48/WH	WireGuard
K234197	FXUWS27-MC605VD-PLT	Motion Sensor with Wireway Cover Kit
P10407	LENS-UWS27	Replacement Lens

PRODUCT DIMENSIONS		
Width- in / (mm)	48" / 1219	
Height- in / (mm)	2.58" / 66	
Depth- in / (mm)	6.90" / 175.3	
IK Rating	-	
Weight (lbs)	6.88	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL/ cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS