naturaled®

Version	2.0	Date	1/16/24
Prepared By	JC		

PRODUCT SPECIFICATION			
Category Cut Off Wall Pack			PICTUR
Item Number	9553		
Stock Code	FXCWP60SW/CCT3/BZ-PHO		
Mounting	Wall		
Housing Color	Bronze		



ELECTRICAL CHARACTERISTICS				
Rated Wattage (W)	28/40/60			
Tested Wattage (W)	63.69	Replacement Wattage (W)	100-250	
Input Voltage (V)	120-277V			
Voltage Frequency (Hz)	50/60	Surge Protect Level	4KV	
Input Current (A)	0.537	Dimmable	0-10V	
Power Factor	>0.9	AUX (12V) Line	No	
THD	<20%	Photocell	Included	

PHOTOMETRIC CHARACTERISTICS					
Lumen (lm)	3,780 5,400 8,176	ССТ (К)	3CCT (30/40/50K)		
Efficacy (lm/w)	136	Beam Angle (°)	Cut Off		
CRI	>70				

GENERAL CHARACTERISTICS			
Operating Temperature (°F)	-40°F ~ 122°		
Storage Temperature (°F)	-40°F ~ 176°		
IP Rating	IP65		
IK Rating	-		
Rated Life (Hrs)	50,000		
Warranty (Yrs)	5		

ACCESSORIES				
ltem #	Stock Code	Description		
7336	BAEM4-60BC/MV-A	4W Emergency Battery Backup Driver		
P10540	SEN-ANT-11-WH	Remote Programmable Microwave Motion Sensor 0-10V		
P10316	SEN-BRI-RC100	Remote Programmer for P10540		

Width- in / (mm)	14.20"	360
Height- in / (mm)	9.25"	235
Depth- in / (mm)	6.50"	166
EPA (ft²)		-
Weight (lbs)	7.	.05
Mounting Height (ft)	10	~20
Cable Length (ft)	1.	.98

<	6.5" (166mm)

CERTIFICATIONS					
JL/ETL UL/cUL CEC					
NSF/ETL Sanitation		JA8			
Energy Star		FCC	\checkmark		
DLC	5.1 Premium	RoHs	\checkmark		

DOCUMENTS			
LM79	\checkmark	IES File	\checkmark
LM80	\checkmark	Dimmer List	

9.25" (235mm)

COMMENTS

PRODUCT DIMENSIONS