

Version	2.0	Date	6/24/2021
Prepared By	C.L.		

PRODUCT SPECIFICATION	
Category	Post Top
Item Number	9571
Stock Code	FX15PST34SW/8CCT3/BK
Mounting	Pole - Fits 2 3/8"-3" Tenon
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	34 / 28 / 20	Replacement Wattage (W)	150
Tested Wattage (W)	34		
Input Voltage (V)	100 ~ 277	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60		
Input Current (A)	0.28 (@120V)	Dimmable	0 ~ 10V
Power Factor	>0.9	AUX (12V) Line	No
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	5262 / 4200 / 3004	CCT (K)	3000 / 4000 / 5000
Efficacy (lm/w)	150	Beam Angle (°)	110
CRI	> 80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°F
Storage Temperature (°F)	-40°F ~ 158°F
IP Rating	IP65
Rated Life	50000
Warranty	5 Years

ACCESSORIES		
Item #	Stock Code	Description
P10389	SPD-L-10KV-277	10KV surge protector - 120 ~ 277V
P10390	SPD-L-20KV-277	20KV surge protector - 120 ~ 277V

PRODUCT DIMENSIONS		
Width- in (mm)	15" (380mm)	
Height- in (mm)	21.65" (550mm)	
Depth- in (mm)	15" (380mm)	
EPA (ft²)	0.582	
Weight (lbs)	8.8	
Mounting Height (ft)	8 ~ 15	
Cable Length (ft)		

QUALIFICATIONS							
UL/ETL	ETL/cETL	CEC		LM79		IES File	✓
NSF/ETL Sanitation		JA8		LM80	✓	Dimmer List	
Energy Star		FCC	✓				
DLC	5.1 Premium	RoHs	✓				

COMMENTS