

Version	2.0	Date	2/6/23
Prepared By	JC		

		PRODUCT S
Category	Bollard	
Item Number	9643	
Stock Code	FX5.5BLD18SW/41FCN/8CCT3/BK	
Mounting	Ground Mounting	
Housing Color	Black (RAL#9005)	




ELECTRICAL CHARACTERISTICS				
Rated Wattage (W)	10/15/18		100	
Tested Wattage (W)	10/15/18	Replacement Wattage (W)		
Input Voltage (V)	120-277V			
Voltage Frequency (Hz)	50/60	Surge Protect Level	10KV	
Input Current (A)	0.16	Dimmable	0-10V	
Power Factor	>0.9	AUX (12V) Line	-	
THD	<20%			

PHOTOMETRIC CHARACTERISTICS				
Lumen (Im)	1,228 1,875 2,251	ССТ (К)	3CCT (30/40/50K)	
Efficacy (lm/w)	125	Beam Angle (°)	360°	
CRI	>80			

GENERAL CHARACTERISTICS				
Operating Temperature (°F)	-40°F ~ 122°F			
Storage Temperature (°F)	-40°F ~ 140°F			
IP Rating	IP65			
Rated Life (Hrs)	50,000			
Warranty (Yrs)	5			

ACCESSORIES				
Item#	Stock Code	Description		
P10068	PLT-5.5BLD/T3/BK	Type 3 Lens Cover		

Diameter of head - in / (mm)	5.5"	140.5
Diameter of body - in / (mm)	5.5"	140.5
Length- in / (mm)	41"	1025
EPA (ft²)		-
Weight (lbs)		11
Mounting Height (ft)		-
Cable Length (ft)		-



CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS				
LM79	✓	IES File	✓	
LM80	✓	Dimmer List		

ഹ	D/I	ME	NTS
CO	IAII	AIL	1413