

Version	2.0	Date	12/28/23
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Wide Vapor Tight
Item Number	9676
Stock Code	VTL11/200S/48FR/8C3/347
Mounting	Surface / Ceiling / Chain
Housing Color	Gray + Frosted PC Lens



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	120/160/200	Replacement Wattage (W)	100-400
Tested Wattage (W)	120/160/200		
Input Voltage (V)	120-347V	Surge Protect Level	6KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	1.82	AUX (12V) Line	Yes
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	19,200 25,600 32,000	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	160	Beam Angle (°)	120°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 158°
IP Rating	IP66
NEMA Rated Enclosure	NEMA - 4X
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7341	BAEM20-260BC/347-A	20W Emergency Battery 120-347V
P10438	SEN-HB001VCR-1	Remote Programmable Microwave Motion Sensor 0-10V Bi-Level
P10323	SEN-HD06R	Remote Programmer

PRODUCT DIMENSIONS		
Width- in / (mm)	49.0" / 1243	
Height- in / (mm)	4.50" / 115	
Depth- in / (mm)	10.50" / 266	
IK Rating	-	
Weight (lbs)	13.9	
Mounting Height (ft)	10~20	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation	✓	JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	
NEMA	✓		

COMMENTS