

TWP TRADITIONAL WALL PACK CCT 3

PROJECT: _____

SCHEDULE: _____ DATE: _____

PREPARE BY: _____

NOTES: _____

DESCRIPTION

naturaLED® TWP traditional wallpack comes in rugged cast-aluminum housing with excellent thermal design. DLC Premium qualified, our TWP product offers a popular classic appearance for your needs. The traditional shape maintains an aesthetic appearance and will replace any building's wallpack or perimeter lighting. Ideal for outdoor applications such as carports, loading areas, driveways, parking area and pathways. Designed for wall mounting above four feet from ground. New available in Wattage Selectable and Color Temperature Selectable option. *Requires an easy installation using the connectors to activate photocell sensor.

APPLICATIONS

Security, Pathway, Perimeter, Entryway, Area Lighting, and building facades

FEATURES

- DLC Premium Qualified
- IP65 Rated
- ETL Listed
- Built In Photocell Sensor Included (Easy connector to activate the photocell)
- ColorTemp: 4000K, 5000K or CCT3
- Dimmable: 0-10V
- Input line voltage: 120-277V, 120-347V
- Input Current: 28W-0.24A, 38W-0.32A, 60W-0.50A, 80W-0.67A, 100W-0.50A
- Surge Protect Level: 4KV
- Material: Die Cast Aluminum
- Lens: Borosilicate Glass Lens
- Corrosion resistant powder coating
- Operating temperature: -40°F - 122°F
- 5 Year Warranty
- Finish: Bronze
- Optional for Purchase: Motion Sensor, Emergency Driver, Wireguard, Replacement Lens, Shield Cover, Surge Protection



Rated Life 50,000 Hours
Warranty 5 Years

ACCESSORIES

	Motion Sensor
	Emergency Drivers
	Wireguard
	Replacement Lens
	Shield Cover
	Surge Protection

SAMPLE NUMBER FXTWP60SW/CCT3/BZ-PHO

FAMILY	SERIES	WATTAGE	SELECTABLE	COLOR TEMP	FINISH COLOR	ACCESSORY
FX Fixture	TWP Traditional Wall Pack	60 28/38/60W	SW Selectable Wattage	CCT3 3000K 4000K 5000K	BZ Bronze	PHO Photocell Included



TRADITIONAL WALL PACK & CCT 3

WALL & AREA LUMINAIRES

ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Color	IP65 Rated	DLC (S/P)
28	9453	FXTWP28/40K/BZ-PHO	4000K	4,200	175	Bronze	•	P
28	9454	FXTWP28/50K/BZ-PHO	5000K	4,200	175	Bronze	•	P
38	9447	FXTWP38/40K/BZ-PHO	4000K	5,700	175-250	Bronze	•	P
38	9448	FXTWP38/50K/BZ-PHO	5000K	5,700	175-250	Bronze	•	P
60	9449	FXTWP60/40K/BZ-PHO	4000K	9,000	250-400	Bronze	•	P
60	9450	FXTWP60/50K/BZ-PHO	5000K	9,000	250-400	Bronze	•	P
80	9451	FXTWP80/40K/BZ-PHO	4000K	12,000	400- 575	Bronze	•	P
80	9452	FXTWP80/50K/BZ-PHO	5000K	12,000	400-575	Bronze	•	P
80	9542	FXTWP80/50K/WH-PHO	5000K	12,000	400-575	White	•	P
28	9455	FXTWP60SW/CCT3/BZ-PHO	3CCT	4,404	175-400	Bronze	•	P
38			(30/40/50K)	6,260	175-400		•	P
60				9,134	175-400		•	P
60	9456	FXTWP100SW/CCT3/BZ-PHO	3CCT	9,065	400-750	Bronze	•	P
80			(30/40/50K)	11,260	400-750		•	P
100				14,500	400-750		•	P
38	9534	FXTWP38/40K/BZ/347-PHO	4000K	5,700	175-250	Bronze	•	P
38	9535	FXTWP38/50K/BZ/347-PHO	5000K	5,700	175-250	Bronze	•	P
60	9536	FXTWP60/40K/BZ/347-PHO	4000K	9,000	250-400	Bronze	•	P
60	9537	FXTWP60/50K/BZ/347-PHO	5000K	9,000	250-400	Bronze	•	P
28	9532	FXTWP60SW/CCT3/BZ/347-PHO	3CCT	4,060	175-400	Bronze	•	P
38			(30/40/50K)	5,510	175-400		•	P
60				8,700	175-400		•	P
60	9533	FXTWP100SW/CCT3/BZ/347-PHO	3CCT	8,700	400-750	Bronze	•	P
80			(30/40/50K)	11,600	400-750		•	P
100				14,500	400-750		•	P

ACCESSORIES (Ordered Separately)

Motion Sensor



P10234 SEN-MC605V-D
(Microwave Motion Photocell Sensor 0-10V)

Shield



P10402 CVR-TWP-SMALL/BZ
(Shield cover- small 28W Bronze, Size: 9.05"x9.20")



P10403 CVR-TWP-MEDIUM/BZ
(Shield cover- medium 38-100W Bronze, Size: 14.30"x9.20")

Wireguard



P10004 WG-TWP-MEDIUM
(Wireguard for Medium TWP
38W,60W,80W,100W,CCT3, Size: 14.30"x9.20")

Surge Protection



P10389 SPD-L-10KV-277
(Surge Protection 10KV 120-277V)



P10390 SPD-L-20KV-277
(Surge Protection 20KV 120-277V)



P10391 SPD-L-20KV-480
(Surge Protection 20KV 347-480V)

Emergency Driver



7336 BAEM4-60BC/MV-A
(4W CEC Compliant LED Emergency Driver for 28W, 38W)



7334 BAEM15-48BC/MV-A
(15W CEC Compliant LED Emergency Driver
for 38W, 60W, 80W, 100W CCT3)



7337 BAEM25-170BC/347-C
(25W Micro Inverter 120-347V with 12" Conduit 100W CCT3)

Replacement Glass Lens



P10002 LENS-TWP-SMALL
(Glass Lens Gasket for 28W, Size: 9.05"x9.20")



P10000 LENS-TWP-MEDIUM
(Glass Lens Gasket for 38-100W, CCT3, Size: 14.30"x9.20")

Replacement Plastic Lens




P10003 LENS-TWP-PC-MEDIUM
(Plastic Lens Gasket for 38-100W, CCT3, Size: 14.30"x9.20")

TRADITIONAL WALL PACK & CCT 3


WALL & AREA LUMINAIRES

DIMENSIONS

28W
5.51-lbs




38W
6.79-lbs




60W
6.86-lbs


CCT3 60W
6.86-lbs



80W
8.07-lbs




CCT3 100W
9.26-lbs



PHOTOMETRICS CHART


28 Watt
DLC Premium



Center Beam fc	Beam Width
2.5R	136 fc 7.8 R 11.7 R
5.0R	34.0 fc 15.6 R 23.4 R
7.5R	15.1 fc 20.5 R 33.1 R
10.0R	8.50 fc 31.3 R 46.8 R
12.5R	5.44 fc 39.1 R 58.5 R
15.0R	3.78 fc 46.9 R 70.3 R

Vert. Spread: 114.8°
HORIZ. Spread: 133.8°


38 Watt
DLC Premium



Center Beam fc	Beam Width
2.5R	182 fc 6.5 R 7.2 R
5.0R	45.4 fc 12.9 R 14.4 R
7.5R	20.2 fc 18.4 R 21.5 R
10.0R	11.5 fc 25.9 R 28.7 R
12.5R	7.26 fc 32.4 R 35.9 R
15.0R	5.04 fc 38.8 R 43.1 R

Vert. Spread: 104.6°
HORIZ. Spread: 110.3°


60 Watt
DLC Premium



Center Beam fc	Beam Width
2.5R	284 fc 6.3 R 5.9 R
5.0R	71.1 fc 12.7 R 11.8 R
7.5R	31.5 fc 18.0 R 17.6 R
10.0R	17.8 fc 25.3 R 23.5 R
12.5R	11.4 fc 31.7 R 29.4 R
15.0R	7.90 fc 38.0 R 35.3 R

Vert. Spread: 103.4°
HORIZ. Spread: 99.3°


80 Watt
DLC Premium



Center Beam fc	Beam Width
2.5R	436 fc 6.8 R 5.8 R
5.0R	109 fc 13.6 R 11.6 R
7.5R	48.5 fc 20.5 R 17.4 R
10.0R	27.3 fc 27.3 R 23.2 R
12.5R	17.5 fc 34.1 R 29.0 R
15.0R	12.1 fc 40.9 R 34.8 R

Vert. Spread: 107.5°
HORIZ. Spread: 98.5°


28/38/60 Watt (CCT)
DLC Premium



Center Beam fc	Beam Width
2.5R	254 fc 6.8 R 7.0 R
5.0R	63.4 fc 13.6 R 13.9 R
7.5R	28.2 fc 20.4 R 20.9 R
10.0R	15.8 fc 27.2 R 27.9 R
12.5R	10.1 fc 34.0 R 34.8 R
15.0R	7.04 fc 40.7 R 41.8 R

Vert. Spread: 107.3°
HORIZ. Spread: 100.7°

60/80/100 Watt (CCT)
DLC Premium



Center Beam fc	Beam Width
2.5R	548 fc 6.9 R 6.5 R
5.0R	137 fc 13.9 R 13.0 R
7.5R	60.9 fc 20.8 R 19.5 R
10.0R	34.3 fc 27.8 R 26.0 R
12.5R	21.9 fc 34.7 R 32.5 R
15.0R	15.2 fc 41.7 R 39.0 R

Vert. Spread: 108.5°
HORIZ. Spread: 104.5°

PACKAGE

Case Qty 1 pc

